



joe — joe@db-2021: ~ — ssh jfrancom@ssh.cs.dixie.edu -L 6571:cleopatra:6571 — 87x23

```
joe@db-2021:~$ sudo apt install mysql-server
```



joe — joe@db-2021: ~ — ssh jfrancom@ssh.cs.dixie.edu -L 6571:cleopatra:6571 — 87x23

```
[joe@db-2021:~$ sudo mysql_secure_installation
```

```
joe@db-2021:~$ sudo mysql_secure_installation
```

Securing the MySQL server deployment.

Connecting to MySQL using a blank password.

VALIDATE PASSWORD COMPONENT can be used to test passwords and improve security. It checks the strength of password and allows the users to set only those passwords which are secure enough. Would you like to setup VALIDATE PASSWORD component?

Press y|Y for Yes, any other key for No: Y



```
joe@db-2021:~$ sudo mysql_secure_installation
```

Securing the MySQL server deployment.

Connecting to MySQL using a blank password.

VALIDATE PASSWORD COMPONENT can be used to test passwords and improve security. It checks the strength of password and allows the users to set only those passwords which are secure enough. Would you like to setup VALIDATE PASSWORD component?

[Press y|Y for Yes, any other key for No: Y

There are three levels of password validation policy:

LOW Length >= 8

MEDIUM Length >= 8, numeric, mixed case, and special characters

STRONG Length >= 8, numeric, mixed case, special characters and dictionary file

Please enter 0 = LOW, 1 = MEDIUM and 2 = STRONG: 2

LOW Length >= 8  
MEDIUM Length >= 8, numeric, mixed case, and special characters  
STRONG Length >= 8, numeric, mixed case, special characters and dictionary  
file

[Please enter 0 = LOW, 1 = MEDIUM and 2 = STRONG: 2  
Please set the password for root here.

[New password:

[Re-enter new password:

Estimated strength of the password: 50

[Do you wish to continue with the password provided?(Press y|Y for Yes, any other key fo  
r No) : Y

By default, a MySQL installation has an anonymous user,  
allowing anyone to log into MySQL without having to have  
a user account created for them. This is intended only for  
testing, and to make the installation go a bit smoother.  
You should remove them before moving into a production  
environment.

Remove anonymous users? (Press y|Y for Yes, any other key for No) : █



[New password:

[Re-enter new password:

Estimated strength of the password: 50

[Do you wish to continue with the password provided?(Press y|Y for Yes, any other key for No) : Y

By default, a MySQL installation has an anonymous user, allowing anyone to log into MySQL without having to have a user account created for them. This is intended only for testing, and to make the installation go a bit smoother. You should remove them before moving into a production environment.

[Remove anonymous users? (Press y|Y for Yes, any other key for No) : Y  
Success.

Normally, root should only be allowed to connect from 'localhost'. This ensures that someone cannot guess at the root password from the network.

Disallow root login remotely? (Press y|Y for Yes, any other key for No) : Y



a user account created for them. This is intended only for testing, and to make the installation go a bit smoother. You should remove them before moving into a production environment.

[Remove anonymous users? (Press y|Y for Yes, any other key for No) : Y  
Success.]

Normally, root should only be allowed to connect from 'localhost'. This ensures that someone cannot guess at the root password from the network.

[Disallow root login remotely? (Press y|Y for Yes, any other key for No) : Y  
Success.]

By default, MySQL comes with a database named 'test' that anyone can access. This is also intended only for testing, and should be removed before moving into a production environment.

Remove test database and access to it? (Press y|Y for Yes, any other key for No) : Y



'localhost'. This ensures that someone cannot guess at the root password from the network.

Disallow root login remotely? (Press y|Y for Yes, any other key for No) : Y  
Success.

By default, MySQL comes with a database named 'test' that anyone can access. This is also intended only for testing, and should be removed before moving into a production environment.

Remove test database and access to it? (Press y|Y for Yes, any other key for No) : Y  
- Dropping test database...  
Success.

- Removing privileges on test database...  
Success.

Reloading the privilege tables will ensure that all changes made so far will take effect immediately.

Reload privilege tables now? (Press y|Y for Yes, any other key for No) : Y





🏠 joe — joe@db-2021: ~ — ssh jfrancom@ssh.cs.dixie.edu -L 6571:cleopatra:6571 — 87x23

```
joe@db-2021:~$ sudo mysql
```

```
mysql> This is the mysql prompt where we will type most of our commands
```